



NEWS

2024
25 |

Decorative



index

GYPSUM COLORING	4
GYPSUM COLORING POINT	12
MORGANA	16
TARA MINI	20
TARA UPS / EMERGENCY	22
REGOLO	24

LINEA LIGHT GROUP

Dalla nascita, nel 1985, ad oggi Linea Light Group è cresciuto fino a diventare ed essere riconosciuto come uno tra i maggiori player per l'illuminazione tecnica e decorativa. Queste due anime convivono e si alimentano a vicenda, grazie alla costante e continua ricerca formale e tecnologica del gruppo.

Con la recente acquisizione dello storico brand Stilnovo, celebre per i suoi prodotti innovativi e sperimentali, si arricchisce l'offerta decorativa di Linea Light Group. Da Stilnovo abbiamo ereditato oggetti luminosi disegnati da Ettore Sottsass e De Pas D'urbino Lomazzi passando per Joe Colombo, a queste icone abbiamo affiancato nuove lampade sviluppate interamente in azienda. L'acquisizione completa la collezione Decòrative composta da prodotti dalla grande personalità e dalla forte presenza scenica.

Contemporaneamente Linea Light Group mantiene la sua presenza di leadership nell'illuminazione professionale con il brand i-LèD, riconosciuto come uno tra i maggiori innovatori in ambito LED. Dal 2019 siamo posizionati nel segmento urban & industrial lighting con prodotti dedicati, rafforzando la nostra presenza nel mercato dell'illuminazione tecnica con prodotti efficienti e innovativi.

La completezza dei nostri cataloghi ci consente di essere presenti e attivi, su canali di vendita diversificati, permettendoci di fornire in maniera ottimale e veloce ogni nostro cliente. Precisione, rapidità e affidabilità sono i caratteri che da sempre definiscono Linea Light Group.

From the time of its establishment in 1985 to the present, Linea Light Group has grown to the point of becoming and being known as one of the major players in technical and decorative lighting. These two spirits co-exist and fuel one another thanks to the group's constant and continuous technological research.

With the recent acquisition of the historic Stilnovo brand, famous for its innovative and experimental products, Linea Light Group's decorative range is enriched. From Stilnovo, we inherited lighting items designed by Ettore Sottsass and De Pas D'urbino Lomazzi, as well as Joe Colombo, and we brought new lights alongside these icons, developed entirely in-house. The acquisition completes the Decòrative collection made up of products with great personality and a strong dramatic presence.

Linea Light Group simultaneously maintains its presence as a leader in professional lighting with the i-LèD brand, acknowledged as one of the major innovators in the LED area. From 2019, we have been in the urban & industrial lighting segment with dedicated products, reinforcing our presence in the technical lighting market with efficient and innovative products.


The completeness of our catalogues allows us to be present and active on diversified sales channels, so we are able to supply all our customers optimally and quickly. Precision, speed and reliability are the characteristics that have always defined Linea Light Group.



INTERNATIONAL GLOBAL SERVICE LIGHT

La presenza globale del gruppo Linea Light è la chiave della nostra dedizione al servizio clienti. Con team operativi su tutti i continenti, siamo pronti a rispondere alle richieste, sia che siano di natura ordinaria o coinvolgano sfide più complesse. Questa struttura globale ci consente di offrire competenze uniche, inclusa la possibilità di organizzare visite in cantiere con i nostri esperti tecnici e commerciali. Ci impegnamo a garantire risposte tempestive e professionali in ogni momento. In cima ai nostri obiettivi, coltiviamo un dialogo continuo con i professionisti dell'illuminazione, al fine di comprendere e soddisfare al meglio le loro esigenze.

Our global presence is the key of our dedication to customer service. With teams operating on every continent, we are ready to respond to requests, whether they are routine in nature or involve more complex challenges. This global structure allows us to offer unique expertise, including the ability to organise site visits with our technical and commercial experts. We are committed to ensuring timely and professional responses at all times. Cultivating a continuous dialogue with lighting professionals, in order to better understand and satisfy their needs, is at the top of our objectives.



- 01** Linea Light HQ & site production, Treviso, Italy
- 02** Baltimore, USA site production (ETL)
- 03** Zhongshan, China site production (CCC)

- 04** Linea Light Milano, Italy
- 05** Linea Light North East, Italy
- 06** Linea Light Rome, Italy
- 07** Linea Light Spain
- 08** Athens, Greece (technical & sales contact)
- 09** Linea Light Deutschland


- 10** Linea Light France
- 11** Linea Light UK
- 12** Dublin, Ireland (technical & sales contact)
- 13** Doha, Qatar (technical & sales contact)
- 14** Linea Light GCC
- 15** Riyadh, Saudi Arabia (technical & sales contact)
- 16** New Delhi, India (technical & sales contact)
- 17** Linea Light Singapore
- 18** Shanghai, China (technical & sales contact)
- 19** Beijing, China (technical & sales contact)




Base in gesso verniciabile.
Anelli intercambiabili in ABS verniciato.

Paintable plaster base.
Interchangeable painted ABS rings.

GYPSUM COLORING




Gypsum Coloring_R1 | V2
powerLED CRI 90 | 198-264 V
6 W DC - 8 W AC



Opt	2700K 761 lmS - 555 lmD
24°	CA029AWHMFL
42°	CA029AWHMMW

Opt	3000K 794 lmS - 591 lmD
24°	CA029AWHWFL
42°	CA029AWHMMW


Gypsum Coloring_R1 | V2
powerLED CRI 90 | 198-264 V
9 W DC - 12 W AC



Opt	2700K 992 lmS - 772 lmD
24°	CA030AWHMFL
42°	CA030AWHMMW

Opt	3000K 1049 lmS - 821 lmD
24°	CA030AWHWFL
42°	CA030AWHMMW

Gypsum Coloring_R1 | V2
powerLED CRI 90 | 24 V
9 W DC



Opt	2700K 992 lmS - 768 lmD
24°	CA030JWHMFL
42°	CA030JWHMMW

Opt	3000K 1049 lmS - 817 lmD
24°	CA030JWHWFL
42°	CA030JWHMMW

Electronics

Gypsum Coloring_R1 9W 24V
KIT0097 DALI/1-10V/PUSH - 1-9 art. - 25


Accessories included

- Screwdriver/extractor
- White round ring (1x)
- Black round ring (1x)
- Painted Gold r. ring (1x)
- Painted Copper r. ring (1x)




* Installation info

Gypsum Coloring_R1 with included driver minimum space required



Finishes Gypsum White




Base in gesso verniciabile.
Anelli intercambiabili in ABS verniciato.

Paintable plaster base.
Interchangeable painted ABS rings.

GYPSUM COLORING




Gypsum Coloring_Q1 | V2
powerLED CRI 90 | 198-264 V
6 W DC - 8 W AC



Opt | 2700K 761 lmS - 555 lmD
 24° CA031AWHMFL
 42° CA031AWHMMW

Opt | 3000K 794 lmS - 591 lmD
 24° CA031AWHWFL
 42° CA031AWHMMW


Gypsum Coloring_Q1 | V2
powerLED CRI 90 | 198-264 V
9 W DC - 12 W AC



Opt | 2700K 992 lmS - 772 lmD
 24° CA032AWHMFL
 42° CA032AWHMMW

Opt | 3000K 1049 lmS - 821 lmD
 24° CA032AWHWFL
 42° CA032AWHMMW

Gypsum Coloring_Q1 | V2
powerLED CRI 90 | 24 V
9 W DC



Opt | 2700K 992 lmS - 768 lmD
 24° CA032JWHMFL
 42° CA032JWHMMW

Opt | 3000K 1049 lmS - 817 lmD
 24° CA032JHWFL
 42° CA032JWHMMW

Electronics

Gypsum Coloring_R1 9W 24V
KIT0097 DALI/1-10V/PUSH - 1-9 art. - 25


Accessories included

Screwdriver/extractor
 White round ring (1x)
 Black round ring (1x)
 Painted Gold r. ring (1x)
 Painted Copper r. ring (1x)



* Installation info

Gypsum Coloring_Q1
with included driver
minimum space
required



Finishes Gypsum White

GYPSUM COLORING

DOWNLIGHTS




Base in gesso verniciabile.
Anelli intercambiabili in ABS verniciato.

Paintable plaster base.
Interchangeable painted ABS rings.

GYPSUM COLORING



Gypsum Coloring_R2 | V2
powerLED CRI 90 | 198-264 V
13 W DC - 15 W AC



Opt | 2700K 1522 lmS - 1142 lmD
 24° CA033AWHMFL
 42° CA033AWHMMW


Opt | 3000K 1588 lmS - 1215 lmD
 24° CA033AWHWFL
 42° CA033AWHMMW

Accessories included


- Screwdriver/extractor
- White round ring (2x)
- Black round ring (2x)
- Painted Gold r. ring (2x)
- Painted Copper r. ring (2x)



*** Installation info**
Gypsum Coloring_R2
with included
drivers - minimum
space required




Finishes Gypsum White




Base in gesso verniciabile.
Anelli intercambiabili in ABS verniciato.

Paintable plaster base.
Interchangeable painted ABS rings.

GYPSUM COLORING



Gypsum Coloring_Q2 | V2
powerLED CRI 90 | 198-264 V
13 W DC - 15 W AC



Opt | 2700K 1522 lmS - 1142 lmD
 24° CA034AWHMFL
 42° CA034AWHMMW


Opt | 3000K 1588 lmS - 1215 lmD
 24° CA034AWHWFL
 42° CA034AWHMMW

Accessories included

- Screwdriver/extractor
- White round ring (2x)
- Black round ring (2x)
- Painted Gold r. ring (2x)
- Painted Copper r. ring (2x)




*** Installation info**
Gypsum Coloring_Q2
with included
drivers - minimum
space required



Finishes Gypsum White

DOWNLIGHTS




Base in gesso verniciabile. Corpo in alluminio verniciato bianco o nero raggrinzante. Anelli intercambiabili in ABS verniciato.

Paintable plaster base. Body in matt white or black painted aluminium. Interchangeable painted ABS rings.

GYPSUM COLORING POINT



Gypsum Coloring Point
powerLED CRI 90 | 198-264 V
8 W DC - 9 W AC




Opt	2700K 992 lmS - 555 lmD
□ 24°	CA035AWHMFL
□ 42°	CA035AWHMMW
■ 24°	CA035ABBMFL
■ 42°	CA035ABBMW

Opt	3000K 1049 lmS - 587 lmD
□ 24°	CA035AWHWFL
□ 42°	CA035AWHMMW
■ 24°	CA035ABBWFL
■ 42°	CA035ABBMMW

Electronics
Gypsum Coloring Focus 9W 24V
KIT0097 DALI/1-10V/PUSH - 1-10 art. - Ⓢ25

Gypsum Coloring Point
powerLED CRI 90 | 24 V
9 W DC



Opt	2700K 992 lmS - 768 lmD
□ 24°	CA035JWHMFL
□ 42°	CA035JWHMMW
■ 24°	CA035JBBMFL
■ 42°	CA035JBBMMW

Opt	3000K 1049 lmS - 817 lmD
□ 24°	CA035JWHWFL
□ 42°	CA035JWHMMW
■ 24°	CA035JBBWFL
■ 42°	CA035JBBMMW

Accessories included
□ White ring (1x)
■ Black ring (1x)
■ Painted Gold ring (1x)
■ Painted Copper ring (1x)



Finishes □ White
■ Black

PROJECTORS

GYPSUM COLORING POINT

PROJECTORS









Corpo in metallo verniciato raggrinzante in cinque varianti colore abbinato al dettaglio spazzolato oro oppure nickel. Il rosone in metallo verniciato riprende la colorazione del corpo lampada. Cavo di alimentazione nero, eccetto la variante bianca che presenta cavo in tinta.

Painted metal body in five matt colours combined with brushed gold or nickel detail. The painted metal ceiling rose matches the colour of the lamp body. Black power cable, except for the white variant which has a matching cable.

MORGANA



Morgana
220-240 V




E27 Max 22 W LED Bulb
(not included)

- CA025AKWEZZ
- CA025AKBEZZ
- CA025AGUEZZ
- CA025AEKEZZ
- CA025ADUEZZ
- CA025AWUEZZ
- CA025AUBEZZ
- CA025AGKEZZ
- CA025AEUEZZ
- CA025ADNEZZ

- Finishes**
- | | | | | |
|---|---|---|--|---|
| White/Brushed Gold | Black/Brushed Gold | Dark Brown/Brushed Gold | Peach/Brushed Gold | Petrol/Brushed Gold |
| White/Brushed Nickel | Black/Brushed Nickel | Dark Brown/Brushed Nickel | Peach/Brushed Nickel | Petrol/Brushed Nickel |








Corpo in alluminio verniciato bianco o nero raggrinzante.
Diffusore in polimetilmetacrilato sabbiato.

Body in matt white or black painted aluminium.
Sandblasted polymethylmethacrylate diffuser.


TARA MINI




Tara Mini

topLED CRI 90 | 220-240 V
7 W DC - 8 W AC

65 | 

□152 | 



Opt | 2700K 1110 lmS - 784 lmD
□ DI | CA026DWHMDI
■ DI | CA026DBBMDI

Opt | 3000K 1168 lmS - 825 lmD
□ DI | CA026DWHWDI
■ DI | CA026DBBWDI

Accessories

KIT0026 Phase-cut dimmer - 100 W
(required for phase-cut)


Finishes  White
 Black



Corpo in alluminio verniciato bianco o nero raggrinzante.
Diffusore in polimetilmetacrilato sabbiato.


Body in matt white or black painted aluminium.
Sandblasted polymethylmethacrylate diffuser.

TARA UPS / EMERGENCY



Tara UPS

topLED CRI 90 | 220-240 V
18 W DC - 19 W AC




Opt	2700K 2173 lmS - 1265 lmD
White DI	CA027KWHMDI
Black DI	CA027KBBMDI

Opt	3000K 2336 lmS - 1360 lmD
White DI	CA027KWHWDI
Black DI	CA027KBBWDI

Tara UPS

topLED CRI 90 | 220-240 V
25 W DC - 26 W AC




Opt	2700K 3003 lmS - 1765 lmD
White DI	CA028KWHMDI
Black DI	CA028KBBMDI

Opt	3000K 3228 lmS - 1898 lmD
White DI	CA028KWHWDI
Black DI	CA028KBBWDI

Tara Emergency

topLED CRI 90 | 220-240 V
25 W DC - 29 W AC




Opt	2700K 3003 lmS - 1765 lmD
White DI	CA028SWHMDI
Black DI	CA028SBBMDI

Opt	3000K 3228 lmS - 1898 lmD
White DI	CA028SWHWDI
Black DI	CA028SBBWDI

Finishes White
 Black



Regolo | V2 | mono-emission
topLED CRI 90 | 220-240 V
12 W DC - 14 W AC





Opt	2700K 1728 lmS - 1093 lmD
□ DI	CA036DWHMDI
■ DI	CA036DBBMDI
■ DI	CA036DGGMDI

Opt	3000K 1858 lmS - 1175 lmD
□ DI	CA036DWHWDI
■ DI	CA036DBBWDI
■ DI	CA036DGGWDI


Corpo in alluminio verniciato bianco, nero o grigio raggrinzante.
Diffusore in policarbonato sabbato.

Body in matt white, black or grey painted aluminium.
Sandblasted polycarbonate diffuser.

REGOLO



Regolo | V2 | mono-emission
topLED CRI 90 | 220-240 V
17 W DC - 19 W AC



Opt	2700K 1647 lms - 2481 lmD
White DI	CA037DWHMDI
Black DI	CA037DBBMDI
Brilliant Grey DI	CA037DGGMDI

Opt	3000K 1771 lms - 2668 lmD
White DI	CA037DWHWDI
Black DI	CA037DBBWDI
Brilliant Grey DI	CA037DGGWDI


Regolo | V2 | mono-emission
topLED CRI 90 | 220-240 V
26 W DC - 30 W AC



Opt	2700K 3920 lms - 2588 lmD
White DI	CA038DWHMDI
Black DI	CA038DBBMDI
Brilliant Grey DI	CA038DGGMDI

Opt	3000K 4215 lms - 2782 lmD
White DI	CA038DWHWDI
Black DI	CA038DBBWDI
Brilliant Grey DI	CA038DGGWDI

Regolo | V2 | mono-emission
topLED CRI 90 | 220-240 V
35 W DC - 39 W AC



Opt	2700K 5199 lms - 3346 lmD
White DI	CA039DWHMDI
Black DI	CA039DBBMDI
Brilliant Grey DI	CA039DGGMDI

Opt	3000K 5590 lms - 3598 lmD
White DI	CA039DWHWDI
Black DI	CA039DBBWDI
Brilliant Grey DI	CA039DGGWDI


Accessories

KIT0026 Phase-cut dimmer - 100 W
(required for phase-cut)

Finishes White Brilliant Grey
 Black



Regolo | V2 | double-emission
 topLED CRI 90 | 220-240 V
 17 W DC - 19 W AC




- | | |
|------|---------------------------|
| Opt | 2700K 2531 lms - 1933 lmD |
| □ DI | CA040DWHMDI |
| ■ DI | CA040DBBMDI |
| ■ DI | CA040DGGMDI |
| Opt | 3000K 2721 lms - 2079 lmD |
| □ DI | CA040DWHWDI |
| ■ DI | CA040DBBWDI |
| ■ DI | CA040DGGWDI |

Corpo in alluminio verniciato bianco, nero o grigio raggrinzante.
 Diffusori in policarbonato sabbiato.
 Solo su Regolo double-emission L 613: sorgenti controllabili separatamente.


REGOLO



Body in matt white, black or grey painted aluminium.
 Sandblasted polycarbonate diffusers.
 Only on Regolo double-emission L613: sources can be controlled separately.




Regolo | V2 | double-emission
 topLED CRI 90 | 220-240 V
 23 W DC - 26 W AC



Opt	2700K 3550 lms - 2724 ImD
□ DI	CA041DWHMDI
■ DI	CA041DBBMDI
■ DI	CA041DGGMDI

Opt	3000K 3817 lms - 2929 ImD
□ DI	CA041DWHWDI
■ DI	CA041DBBWDI
■ DI	CA041DGGWDI



Regolo | V2 | double-emission
 topLED CRI 90 | 220-240 V
 35 W DC - 38 W AC



Opt	2700K 5300 lms - 3964 ImD
□ DI	CA042DWHMDI
■ DI	CA042DBBMDI
■ DI	CA042DGGMDI

Opt	3000K 5699 lms - 4262 ImD
□ DI	CA042DWHWDI
■ DI	CA042DBBWDI
■ DI	CA042DGGWDI

Regolo | V2 | double-emission
 topLED CRI 90 | 220-240 V
 46 W DC - 51 W AC



Opt	2700K 7090 lms - 5383 ImD
□ DI	CA043DWHMDI
■ DI	CA043DBBMDI
■ DI	CA043DGGMDI

Opt	3000K 7624 lms - 5788 ImD
□ DI	CA043DWHWDI
■ DI	CA043DBBWDI
■ DI	CA043DGGWDI

Accessories

KIT0026 Phase-cut dimmer - 100 W
 (required for phase-cut)

Finishes □ White ■ Brilliant Grey
 ■ Black














Codes index



























Code	Page	Code	Page
CA025ADNEZZ	17	CA034AWHMMW	11
CA025ADUEZZ	17	CA034AWHWFL	11
CA025AEKEZZ	17	CA034AWHMMW	11
CA025AEUEZZ	17	CA035ABBMFL	13
CA025AGKEZZ	17	CA035ABBMMW	13
CA025AGUEZZ	17	CA035ABBWFL	13
CA025AKBEZZ	17	CA035ABBWMW	13
CA025AKWEZZ	17	CA035AWHMFL	13
CA025AUBEZZ	17	CA035AWHMMW	13
CA025AWUEZZ	17	CA035AWHWFL	13
CA026DBBMDI	21	CA035AWHMMW	13
CA026DBBWDI	21	CA035JBBMFL	13
CA026DWHMDI	21	CA035JBBMMW	13
CA026DWHWDI	21	CA035JBBWFL	13
CA027KBBMDI	23	CA035JBBWMW	13
CA027KBBWDI	23	CA035JWHMFL	13
CA027KWHMDI	23	CA035JWHMMW	13
CA027KWHWDI	23	CA035JWHWFL	13
CA028KBBMDI	23	CA035JWHMMW	13
CA028KBBWDI	23	CA036DBBMDI	24
CA028KWHMDI	23	CA036DBBWDI	24
CA028KWHWDI	23	CA036DGGMDI	24
CA028SBBMDI	23	CA036DGGWDI	24
CA028SBBWDI	23	CA036DWHMDI	24
CA028SWHMDI	23	CA036DWHWDI	24
CA028SWHWDI	23	CA037DBBMDI	25
CA029AWHMFL	5	CA037DBBWDI	25
CA029AWHMMW	5	CA037DGGMDI	25
CA029AWHWFL	5	CA037DGGWDI	25
CA029AWHMMW	5	CA037DWHMDI	25
CA030AWHMFL	5	CA037DWHWDI	25
CA030AWHMMW	5	CA038DBBMDI	25
CA030AWHWFL	5	CA038DBBWDI	25
CA030AWHMMW	5	CA038DGGMDI	25
CA030JWHMFL	5	CA038DGGWDI	25
CA030JWHMMW	5	CA038DWHMDI	25
CA030JWHWFL	5	CA038DWHWDI	25
CA030JWHMMW	5	CA039DBBMDI	25
CA031AWHMFL	7	CA039DBBWDI	25
CA031AWHMMW	7	CA039DGGMDI	25
CA031AWHWFL	7	CA039DGGWDI	25
CA031AWHMMW	7	CA039DWHMDI	25
CA032AWHMFL	7	CA039DWHWDI	25
CA032AWHMMW	7	CA040DBBMDI	26
CA032AWHWFL	7	CA040DBBWDI	26
CA032AWHMMW	7	CA040DGGMDI	26
CA032JWHMFL	7	CA040DGGWDI	26
CA032JWHMMW	7	CA040DWHMDI	26
CA032JWHWFL	7	CA040DWHWDI	26
CA032JWHMMW	7	CA041DBBMDI	27
CA033AWHMFL	9	CA041DBBWDI	27
CA033AWHMMW	9	CA041DGGMDI	27
CA033AWHWFL	9	CA041DGGWDI	27
CA033AWHMMW	9	CA041DWHMDI	27
CA034AWHMFL	11	CA041DWHWDI	27

Code	Page
CA042DBBMDI	27
CA042DBBWDI	27
CA042DGGMDI	27
CA042DGGWDI	27
CA042DWHMDI	27
CA042DWHWDI	27
CA043DBBMDI	27
CA043DBBWDI	27
CA043DGGMDI	27
CA043DGGWDI	27
CA043DWHMDI	27
CA043DWHWDI	27
KIT0026	21
	25
	27
KIT0097	5
	7
	13

Finishes

	Gypsum White
	White RAL 9003
	Black RAL 9005
	Brilliant Grey RAL 9006
	Peach RAL 3012
	Petrol RAL 6004
	Dark Brown
	Brushed Gold
	Brushed Nickel

How to read symbols

	Apparecchio a incasso Recessed light		Indice di protezione (IEC 60529) da corpi estranei e acqua Protection index (IEC 60529) against foreign bodies and water
	Proiettore Projector		Foro d'installazione circolare Circular installation hole
	Sospensione Pendant light		Fascio luminoso orientabile Directional light beam
	Lampada a soffitto/parete Ceiling/wall light		Cavo d'alimentazione incluso Power supply cable included
	Lampada a parete Wall light		Driver incluso Driver included
	Installazione in ambiente interno Indoor installation		Driver non incluso Driver not included
	Installazione a soffitto Ceiling mounting		Classe I - classe di isolamento elettrico (IEC) Class I - IEC protection class
	Installazione a soffitto o a parete Ceiling or wall mounting		Classe II - classe di isolamento elettrico (IEC) Class II - IEC protection class
	Installazione a parete Wall mounting		Classe III - classe di isolamento elettrico (IEC) Class III - IEC protection class
	Emissione diretta - apparecchio ad incasso Direct emission - recessed light		C.V. Constant Voltage
	Emissione diretta - lampada a soffitto Direct emission - ceiling light		Phase-cut
	Emissione puntuale - proiettore Punctual emission - projector		
	Emissione diretta - sospensione Direct emission - pendant		
	Monoemissione a parete Monoemission on wall		
	Biemissione a parete Double emission on wall		

Tutti gli articoli sono in classe energetica A++.
Gli schemi di collegamento per gli articoli dell'elettronica sono disponibili all'interno della documentazione tecnica.

All articles belong to energy class A++.
The connection diagrams for electronics articles are included in the technical documentation.

Il dato lumen è calcolato sulla finitura più chiara. I disegni, le quote, i materiali ed i colori del presente catalogo si intendono a titolo indicativo. Nell'interesse della clientela, l'Azienda si riserva il diritto di modificare i modelli in ogni momento senza l'obbligo di preavviso.

"Linealight Group" si riserva il diritto, senza alcun preavviso di modificare le caratteristiche dei propri prodotti come la disponibilità degli stessi in qualunque momento. Tutti i prodotti, relativi dati tecnici, illustrazioni e informazioni presenti sul catalogo non sono vincolanti per "Linealight Group". "Linealight Group" non risponderà di eventuali errori illustrativi, testuali e/o di traduzione. Ulteriori caratteristiche dei prodotti sono contenute nelle relative schede tecniche e fogli istruzione. Il presente catalogo è tutelato dalla legge sui diritti d'autore (legge 22/04/1941 n. 633 e della legge 14/12/1942 n. 1485: di esso è proibita ogni riproduzione totale o anche parziale). Tutti i valori riportati a catalogo sono valori di misurazione. I dati di flusso, CCT e potenza sono passibili di tolleranze di +/- 10%.

The lumen data is calculated on the lightest finish. The drawings, the measurements, the materials and the colours in this catalogue are understood to be indicative. In the interest of the clientele, the company reserves the right to modify the models at any time and without any obligation of advance notice.

"Linea Light Group" reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information in the catalogue are binding for "Linea Light Group". "Linea Light Group" will not be held liable for any illustration, text and/or translation errors. More product characteristics are contained in the relative technical data sheets and instruction sheets. This catalogue is protected by copyright (law 22/04/1941 No. 633 and law 14/12/1942 No. 1485: this prohibits any reproduction, total or even partial).

All values indicated in the catalogue are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Addresses

Linea Light HQ Italy

Via Europa, 14
31028 Vazzola TV
Italy

+39 0438 444826
info@linealight.com

Linea Light Milano

Via Giovanni Boccaccio, 15/A
20121 Milano MI
Italy

+39 02 36750915
milano@linealight.com

Linea Light Nord-Est

Via Medoaco 4
c/o Hope Center
35135 Padova PD
Italy
+39 049 7969440
nordest@linealight.com

Linea Light Roma

Via La Spezia, 34
00182 Roma
Italy

+39 06 68589134
info@linealightroma.com

Linea Light UK

Suite205 The business design center
52 Upper Street Islington
N10QH London
United Kingdom
+44 0203 6371983
info@linealight.co.uk

Linea Light France

Rue des Pays-Bas 12
68310 Wittelsheim
France

+33 389 75 52 23
info@linealight.fr

Linea Light Deutschland

Aktienstraße 214
45473 Mülheim an der Ruhr
Germany

+49 208 299979-0
service@linealight.de

Linea Light Greece

538 Vouliagmenis Ave.
17456 Alimos Athens
Greece

+30 210 9940559
g.virinis@linealight.com

Linea Light Spain

C/ Longares, 48
28022 Madrid
Spain

+34 912534773
gestion@linealight.com

Linea Light USA - Inter Lux

3741 Commerce Drive - Suites 306-308
MD21227 Baltimore
USA

+1 410 381 1497
answers@inter-lux.com

Linea Light GCC

P.O. Box 125902
Jumeirah Lake Towers JBC2
35th Floor Office 04
Dubai UAE
+971 4 4218275
info@linealight.ae

Linea Light Asia - Pacific

No. 7, Nanyi Huayuan Road,
Industry Avenue, 528478 Xiaolan Town,
Zhongshan City, Guangdong Province
China
+86 760 87618355
info@linealight.com.cn

Linea Light Singapore

21 Kaki Bukit Place, 5th Fl.
416199 Singapore
Singapore

+65 6908 5758
info.sg@linealight.com





LIGHT UP NEW IDEAS!

linealight.com